
SAGE



Shelf lighting
SAGE





- Plug & play(external power supply)
- Easy installation option
- Short-term shipment with customized length
- Lifetime: 50,000hrs (ta=95°F, 35°C)
- Ta: -13°F~95°F(-25°C~35°C)
- 3W/ft,300lm/ft(@SAGE)
  4W/ft,420lm/ft(@ SAGE FROST)
- Material: Aluminum alloy
- Other color temp available

Dimensions: (inches/mm)


PCB inside Minimum Cuttable Length:
Flat :3.9"(100mm)
Round Milky:2"(50mm)


SAGE





SAGE FROST





How to order using our catalog numbers
Example: SAGE-R3440K

Series	Lens	Length*	CCT (K)	Energy Efficiency	Finish	Input Cable Length
SAGE	**[blank]** - Flat **R** - Round Milky	**21** - 20.7"(526mm) **33** - 32.5"(826mm) **45** - 44.3"(1126mm)	**30K** - 3000K **40K** - 4000K	**[blank]** - 4W/ft **3** - 3W/ft	**[blank]** - Natural aluminum	**[blank]** - 24"


* Other lengths available

Specifications

Catalog No.	Model	Rated Input (VDC)	Ra	Power (W)	Luminous flux (TYP@4000K)lm	75W (NA159-7524LA-12A6)
SAGE-2130K3 SAGE-2140K3	SAGE-L35-24V	24	85	5	500	13pcs[1]
SAGE-3330K3 SAGE-3340K3	SAGE-L56-24V	24	85	8	800	8pcs[1]
SAGE-4530K3 SAGE-4540K3	SAGE-L77-24V	24	85	11	1100	6pcs[1]
SAGE-R2130K SAGE-R2140K	SAGE FROST-L70-24V	24	85	6.7	705	9pcs[1]
SAGE-R3330K SAGE-R3340K	SAGE FROST-L112-24V	24	85	10.7	1125	6pcs[1]
SAGE-R4530K SAGE-R4540K	SAGE FROST-L154-24V	24	85	14.7	1545	4pcs[1]


* Included: 1pc LED fixture, 2pcs Screws, 2pcs Mounting clips.
[1]: Max. Pcs Per UL Listed LED Power Supply.

Photometrics




Accessories	Catalog No.	Description	Length (inch)

NA159-7524LA-12A6



Model: SLT75-24VL-2A
Matching driver, max. 75W.
Input: 100-120VAC NA plug 1 + 59" cable.
Output: 24VDC 12-way splitter JB-12A + 6"cable.

NA383-9624DLA-DG6-12A6




Model: SLD96-24VC-UN1-A
Matching 1-10V dimmable driver, max. 96W.
Input: 120-250VAC NA3 plug + 83" cable.
Output: 24VDC DG238 DEGSON connector + 6" cable + 12-way splitter JB-12A + 6" cable.

Accessories (optional)

Catalog No.	Description	Length (inch)
MC-AR (included)	 0° mounting clip x 2	-
MMC-SAGE	 0° mounting clip x 2	-
MMC-AR	 0° magnetic mounting clip x 2	-
MMC45-AR	 45° magnetic mounting clip x 2	-

Installation

Non-magnetic mounting installation



Magnetic mounting installation

